# AGVM 24-230 GEX | 2400 W angle grinder with AVS and kickback protection

- Milwaukee® B-Guard protects both operator and machine from “kickback” effect.
- 4 m rubber cable.
- Powerful, 2400 W “PROTECTOR-MOTOR” with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Autobalancer for greatly reduced vibration of bad discs.
- AVS equipped motor housing and additional AVS side handle for more comfortable handling and less strain of body joints.
- Lowest vibration in it's class with only 2.5 m/s².
- 7 position rotatable main handle.

| | AGVM 24-230 GEX |
|---|---|
| Anti-kickback protection | Yes |
| AVS Anti-Vibration System | Yes |
| Disc diameter (mm) | 230 |
| Line lock out function | Yes |
| Max. cutting depth (mm) | 68 |
| No load speed (rpm) | 6600 |
| Power input (W) | 2400 |
| Rotatable main handle | Yes |
| Sound power level (dB(A)) | 104 |
| Sound power level uncertainty (dB(A)) | 3 |
| Sound pressure level (dB(A)) | 93 |
| Sound pressure level uncertainty (dB(A)) | 3 |
| Spindle size | M 14 |
| Standard equipment | Quick release safety guard, AVS side handle, Autobalancer, FIXTEC flange nut, 4 m cable |
| Supplied in | – |
| Variable speed | No |
| Vibration grinding (m/s²) | 2.5 |
| Vibration grinding uncertainty (m/s²) | 1.5 |
| Vibration sanding (m/s²) | <2.5 |
| Vibration sanding uncertainty (m/s²) | 1.5 |
| Weight (kg) | 5.8 |