M12 BRAID-0 | M12™ sub compact right angle impact driver

- Compact right angle impact driver measures 287 mm in length making it ideal for working within confined spaces.
- Flexible battery system: works with all Milwaukee® M12™ batteries.
- REDLINK™ overload protection electronics delivers best in class system durability.
- Full metal gearbox and gears for superior durability and maximum torque of 68 Nm.
- Compact head design with diameter of 35.6 mm.
- Multi-handle design for multiple hand positions and maximum comfort.
- ¼″ Hex chuck for quick easy one handed bit change.

	M12 BRAID-0
Battery pack capacity (Ah)	–
Battery type	Li-ion
Charger supplied	–
Impact rate (ipm)	0 - 3300
Max. fastening torque (Nm)	68
Max. torque (Nm)	68
No load speed (rpm)	0 - 2425
No. of batteries supplied	0
Sound power level measured (dB(A))	102.9
Sound power level measured uncertainty (dB(A))	3
Sound pressure level (dB(A))	91.9
Sound pressure level uncertainty (dB(A))	3
Supplied in	–
Vibration Impact tightening of fasteners of the maximum capacity of the tool [m|s²]	11
Vibration Impact tightening of fasteners of the maximum capacity of the tool uncertainty [m|s²]	1.5
Voltage (V)	12
Weight with battery pack (kg)	1.2