# M18 BID-402C | M18™ compact ¼˝ Hex impact driver

- Compact impact driver measures 140 mm in length making it ideal for working within confined spaces.
- Milwaukee® high performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Heavy duty full metal gearbox and gears for superior durability and maximum torque.
- ¼˝ Hex drive with click lock for single hand loading of bit.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light.

| | M18 BID-402C |
|---|---|
| Battery pack capacity (Ah) | 4.0 |
| Battery type | Li-ion |
| Charger supplied | 80 min |
| Impact rate (ipm) | 0 - 2450/0 - 3450 |
| Max. torque (Nm) | 180 |
| No load speed (rpm) | 0 - 2000/0 - 2750 |
| No. of batteries supplied | 2 |
| Sound power level (dB(A)) | 104.8 |
| Sound power level uncertainty (dB(A)) | 3 |
| Sound pressure level (dB(A)) | 93.8 |
| Sound pressure level uncertainty (dB(A)) | 3 |
| Standard equipment | Belt hook |
| Supplied in | Kitbox |
| Vibration screw driving (m/s²) | 12.3 |
| Vibration screw driving uncertainty (m/s²) | 2.77 |
| Voltage (V) | 18 |
| Weight with battery pack (kg) | 1.7 |