HD18 PD-0 | M18™ percussion drill

- With its Milwaukee® 4-pole frameless motor it delivers 85 Nm of torque, ideal for powering through the toughest of applications.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all Milwaukee® M18™ batteries.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Full metal gear box delivers maximum performance and long life.
- Heavy Duty 13 mm full metal chuck delivers optimum bit retention.
- Hammer mechanism delivers 28,000 bpm for highly effective masonry drilling.

	HD18 PD-0
Battery pack capacity (Ah)	–
Battery type	Li-ion
Charger supplied	–
Chuck capacity (mm)	13
Max. drilling masonry (mm)	16
Max. drilling steel (mm)	13
Max. drilling wood (mm)	55
Max. percussion rate (bpm)	28,000
Max. torque (Nm)	85
No load speed gear 1 (rpm)	0 - 450
No load speed gear 2 (rpm)	0 - 1800
No. of batteries supplied	0
Sound power level (dB(A))	97.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	86.5
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Side handle, belt clip
Supplied in	–
Vibration drilling into concrete [m|s²]	11.6
Vibration drilling into concrete uncertainty [m|s²]	1.5
Vibration drilling into Metal [m|s²]	<2.5
Vibration drilling into metal uncertainty [m|s²]	1.5
Vibration screw driving (m/s²)	<2.5
Vibration screw driving uncertainty (m/s²)	1.5