M18 CHIWP12-502X | M18 FUEL™ ½˝ high torque impact wrench with pin detent

- The M18 FUEL™ high torque impact wrench pneumatic fastening performance - up to 813 Nm max. fastening torque and up to 1354 Nm nut-busting torque.
- The Milwaukee® DRIVE CONTROL™ allows the user to shift into two different speed and torque settings to maximise application versatility.
- Milwaukee® designed and built brushless POWERSTATE™ motor for longer motor life and more power.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- ½˝ square detent pin.

	M18 CHIWP12-502X
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
Charger supplied	59 min
Impact rate (ipm)	0 - 1700 / 0 - 2300
Max. fastening torque (Nm)	474 / 813
No load speed (rpm)	0 - 1200 / 0 - 1700
No. of batteries supplied	2
Nut-busting torque (Nm)	1354
Sound power level (dB(A))	105.4
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	94.4
Sound pressure level uncertainty (dB(A))	3
Supplied in	HD Box
Vibration screw driving (m/s²)	11.08
Vibration screw driving uncertainty (m/s²)	1.5
Voltage (V)	18
Weight with battery pack (kg)	3.2