M18 ONESLSP-0 | M18™ ONE-KEY™ LED compact site light

- ONE-KEY™ tool customisation allows user to control brightness and set light settings remotely.
- Up to 8 hours of run time on low setting when powered by an M18™ REDLITHIUM-ION™ 5.0 Ah battery pack.
- Highly durable and impact resistant polycarbonate lens to protect the light from rough jobsite conditions.
- IP54 rating in battery mode - light is protected from dust and splashing water.
- Security cable included.
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- Optimise brightness and run time by adjusting the light output between 0 - 4400 Lumens.

	M18 ONESLSP-0
Battery compatibility	All Milwaukee® M18™ batteries
Battery pack capacity (Ah)	—
Battery type	Li-ion
Charger supplied	—
Max. light output High/Medium/Low/Strobe (Lumens)	4400 / 2100 / 1000 / -
Max. run time with M18 B5 battery (h)	2 / 4 / 8 / -
No. of batteries supplied	0
Standard equipment	security cable
Supplied in	–
System	M18
Voltage (AC) (V)	220 - 240
Voltage (DC) (V)	18
Voltage (V)	110V - 240V
Weight with battery pack (kg)	5.4