HD28 SX-502C | M28™ SAWZALL®

- Milwaukee®'s high performance motor delivers maximum power whilst (optimising) maximising the power to weight ratio.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Milwaukee® patented FIXTEC clamp for fast and easy keyless blade change.
- Gear protection clutch - protects the gearbox in case of blade lock ups.

	HD28 SX-502C
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
Charger supplied	90 min
Max. cutting depth in aluminium (mm)	25
Max. cutting depth in metal pipe (mm)	150
Max. cutting depth in non-ferrous metal (mm)	25
Max. cutting depth in soft-wood (mm)	300
Max. cutting depth in steel (mm)	25
No load stroke rate (spm)	0-2000/0-3000
No. of batteries supplied	2
Sound power level (dB(A))	94
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	83
Sound pressure level uncertainty (dB(A))	3
Standard equipment	2 x Super SAWZALL® blades
Stroke length (mm)	28.6
Supplied in	Kitbox
Vibration cutting (m/s²)	16.8
Vibration cutting uncertainty (m/s²)	1.5
Voltage (V)	28
Weight with battery pack (kg)	4.1