HD28 MS-0 | M28™ metal dry cut saw

- Milwaukee®'s high performance motor delivers 3200 rpm for fast cutting.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Premium 174 mm carbide blade.
- Supplied with 36 tooth blade.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Large cutting depth of 61 mm.
- Compact, ergonomic design provides superior control over standard metal saws, reciprocating saws and band saws.

	HD28 MS-0
Battery pack capacity (Ah)	—
Battery type	Li-ion
Blade diameter (mm)	174
Bore size (mm)	20
Charger supplied	—
Max. cutting capacity in steel plate (mm)	5
Max. cutting capacity metal pipe Ø (mm)	61
Max. cutting capacity sections (mm)	61
Max. cutting depth (mm)	61
No load speed (rpm)	3200
No. of batteries supplied	0
Sound power level (dB(A))	94.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	83.5
Sound pressure level uncertainty (dB(A))	3
Supplied in	–
Vibration level (m/s²)	<2.5
Vibration uncertainty (m/s²)	1.5
Voltage (V)	28
Weight (kg)	3.30
Weight with battery pack (kg)	4.2