HD18 CS-402B | M18™ 55 mm circular saw for wood and plastic

- Milwaukee® powerful 3500 rpm motor easily cuts most timber construction materials.
- Flexible battery system: works with all Milwaukee® M18™ batteries.
- Supplied with 24 tooth saw blade, parallel guide, dust port and allen key.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Large 50° bevel facility.
- Magnesium upper and lower guards provide best in class durability for impact resistance.
- Excellent visibility of cutting line.

	HD18 CS-402B
Battery pack capacity (Ah)	4.0
Battery type	Li-ion
Blade diameter (mm)	165
Bore size (mm)	15.87
Charger supplied	80 min
Max. cutting depth 45° (mm)	39
Max.cutting depth 90° (mm)	55
No load speed (rpm)	3500
No. of batteries supplied	2
Sound power level (dB(A))	93
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	83
Sound pressure level uncertainty (dB(A))	3
Standard equipment	24 tooth saw blade, parallel guide, dust port, allen key, key, rip fence
Supplied in	Tool bag
Vibration level (m/s²)	<2.5
Vibration uncertainty (m/s²)	1.5
Voltage (V)	18
Weight with battery pack (kg)	3.8