M12 CCS44-602X | M12 FUEL™ sub compact circular saw

- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 2x longer motor life and up to 2x more cuts per charge.
- Flexible battery system: works with all Milwaukee® M12™ batteries.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- 50° bevel capacity.
- Magnesium upper and lower guards provide best in class durability for impact resistance.

	M12 CCS44-602X
Battery pack capacity (Ah)	6.0
Battery type	Li-ion
Blade diameter (mm)	140
Bore size (mm)	20
Charger supplied	90 min
Max. cutting depth 45° (mm)	33
Max.cutting depth 90° (mm)	44
No load speed (rpm)	3600
No. of batteries supplied	2
Sound power level measured (dB(A))	93.0
Sound power level measured uncertainty (dB(A))	3.0
Sound pressure level (dB(A))	82.0
Sound pressure level uncertainty (dB(A))	3.0
Standard equipment	Circular saw blade, side fence
Supplied in	HD Box
Vibration sawing of wood [m|s²]	1.46
Vibration sawing of wood uncertainty [m|s²]	1.5
Vibration sawing uncertainty [m|s²]	1.5
Voltage (V)	12
Weight with battery pack (kg)	2.7