M18 BMT-421C | M18™ multi-tool

- Up to 50% faster and versatile cordless solution for cutting and removal applications with corded performance.
- REDLINK™ overload protection and constant speed electronics in tool deliver best in class durability and performance.
- 12 variable speed settings from 12,000 - 18,000 orbits per minute and 3.4° oscillation movement allows quick completion of professional applications into materials such as metal, wood and plastic.
- Productivity enhancing FIXTEC tool free blade change with universal blade change adaptor included to accept all competitor blades.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Unique cutting depth stop adaptor to prevent over-cutting in material.
- Unique dust extraction kit to keep the work space dust-free when connected to an AC or DC extraction system.

	M18 BMT-421C
Battery pack capacity (Ah)	1 x 2.0 + 1 x 4.0
Battery type	Li-ion
Charger supplied	80 min
No load speed (rpm)	12,000 - 18,000
No. of batteries supplied	2
Oscillation angle left/ right (°)	1.7
Sound power level (dB(A))	90.8
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	79.8
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Blade, sanding pad, UL blade adapter, blade adapter, clamp shaft, 5 x sanding paper,dust port assembly, depth gauge, blade guard
Supplied in	Kitbox
Vibration cutting wood (m/s²)	12.3
Vibration cutting wood uncertainty (m/s²)	1.5
Vibration sanding (m/s²)	3.6
Vibration sanding uncertainty (m/s²)	1.5
Voltage (V)	18
Weight with battery pack (kg)	1.7