M18 SMS216-401 | M18™ 216 mm mitre saw

- Milwaukee® powerful frameless motor delivers 2700 rpm for fast cutting.
- Spindle lock - for quick and easy blade change.
- Heavy duty cast base and fence ensures durability and accuracy.
- 48°/-2° bevel capacity.
- Supplied with saw blade (48 teeth), blade spanner and work clamp.
- Flexible battery system: works with all Milwaukee® M18™ batteries.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.

	M18 SMS216-401
Battery pack capacity (Ah)	4.0
Battery type	Li-ion
Bevel capacity left (°)	48
Bevel capacity right (°)	-2
Blade diameter (mm)	216
Bore size (mm)	30
Charger supplied	80 min
Max. cutting capacity 45° mitre/ 45° bevel (mm)	190 x 48
Max. cutting capacity 45° mitre/ 90° bevel (mm)	190 x 60
Max. cutting capacity 90° mitre/ 45° bevel (mm)	270 x 48
Max. cutting capacity 90° mitre/ 90° bevel (mm)	270 x 60
Mitre capacity left (°)	50
Mitre capacity right (°)	50
No load speed (rpm)	2700
No. of batteries supplied	1
Sound power level (dB(A))	101
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	88
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Blade, blade spanner, work clamp
Supplied in	–
Vibration sawing of wood [m|s²]	1.9
Vibration sawing of wood uncertainty [m|s²]	1.5