PD2E 24 RS | 1010 W 2-speed percussion drill

- Powerful 1010 W motor.
- Electronics with variable speed selection and reverse function.
- AVS (Anti-Vibration-System) and soft grip for more comfortable use.
- Metal synchromesh gearbox for outstanding durability.
- Direct bit reception for reduced length and weight for best visibility during screw driving.
- Safety clutch to protect the user.
- Keyless chuck 1.5 - 13 mm.

	PD2E 24 RS
Chuck capacity (mm)	13
Max. drilling concrete (mm)	20
Max. drilling masonry (mm)	24
Max. drilling steel (mm)	16
Max. drilling wood (mm)	40
Max. static stalling torque (Nm)	54
No load speed gear 1 (rpm)	0 - 1450
No load speed gear 2 (rpm)	0 - 3400
Power input (W)	1010
Sound power level (dB(A))	112
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	101
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Additional handle with metal depth gauge
Supplied in	Kitbox
Vibration drilling (m/s²)	21.9
Vibration drilling into Metal [m|s²]	4
Vibration drilling into metal uncertainty [m|s²]	1.5
Vibration drilling uncertainty (m/s²)	3.3
Weight (kg)	3.1