M12 BI-0 | M12™ sub compact inflator

- Compact lightweight design for fast inflation of car, light truck and compact equipment tires.
- High efficiency motor & pump.
- Anti-vibration stand with all rubber feet for no movement while inflating.
- Auto shut-off technology inflates to users pre-selected pressure for highly accurate inflation.
- Illuminated LCD display with a digital pressure and fuel gauge that displays remaining charge.
- Nozzle & hose storage, easily stores 66 cm hose and attachments, with an all-brass schrader chuck.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life (Battery sold separately).

	M12 BI-0
Battery pack capacity (Ah)	-
Battery type	Li-ion
Charger supplied	—
Dimensions (mm)	190.5 x 165.1
Duty cycle	50% at 10 min On and 10 min Off
Gauge accuracy (%)	±3%
Hose length (mm)	660
Max. pressure (bar / PSI)	8.27 / 120
No load air delivery (l/min)	24.9
No. of batteries supplied	0
Standard equipment	1x ball inflation needle, 1x presta chuck, 1x inflator nozzle, 1x schrader chuck
Supplied in	–
Voltage (V)	12
Weight with battery pack (kg)	1.6