C12 RT-0 | M12™ sub compact rotary tool

- Versatile cordless solution for cutting and removal applications.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Variable speed (5000 - 32,000 rpm).
- 3.2 mm collet fits most current accessories in the market.
- Spindle lock mechanism for easy accessory changes.
- Superior ergonomics and lightweight.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.

	C12 RT-0
Battery pack capacity (Ah)	–
Battery type	Li-ion
Charger supplied	–
Collet capacity (mm)	3.2
No load speed (rpm)	5000 - 32,000
No. of batteries supplied	0
Sound power level (dB(A))	84
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	73
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Bare unit only
Supplied in	–
Vibration cutting (m/s²)	3.4
Vibration cutting uncertainty (m/s²)	1.5
Vibration drilling into Metal [m|s²]	2.4
Vibration drilling into metal uncertainty [m|s²]	1.5
Vibration grinding (m/s²)	3.1
Vibration grinding uncertainty (m/s²)	1.5
Vibration sanding (m/s²)	2.6
Vibration sanding uncertainty (m/s²)	1.5
Voltage (V)	12
Weight (kg)	0.44
Weight with battery pack (kg)	0.6