# AGS 15-125 C | 1500 W grinder/sander

- Powerful, 1500 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Aligned to the optimum speed for flap grinding discs.
- Constant power electronics providing constant speed under load.
- Soft start for smooth start up.
- Line lock out function to prevent automatic start up after power breakdown.
- Motor overload protection.
- Burst resistant and tool-free quick release safety guard for fast adjustment.

| | AGS 15-125 C |
|---|---|
| Line lock out function | Yes |
| No load speed (rpm) | 7600 |
| Power input (W) | 1500 |
| Sound power level (dB(A)) | 97 |
| Sound power level uncertainty (dB(A)) | 3 |
| Sound pressure level (dB(A)) | 86 |
| Sound pressure level uncertainty (dB(A)) | 3 |
| Spindle size | M 14 |
| Standard equipment | Quick release safety guard, side handle, flange, flange nut, spanner, 4 m cable, filter grill |
| Supplied in | – |
| Vibration grinding (m/s²) | 5.6 |
| Vibration grinding uncertainty (m/s²) | 1.5 |
| Vibration sanding (m/s²) | 2.8 |
| Vibration sanding uncertainty (m/s²) | 1.5 |
| Weight (kg) | 2.4 |