M18 CH-502C | M18 FUEL™ SDS-plus hammer

- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 2x longer motor life and up to 25% more power.
- Compatible with M18 CDE dust extractor.
- REDLINK PLUS™ intelligence system delivers the most advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM-ION™ battery pack delivers up to 2.5x more run time, up to 20% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies.
- Second hardest hitting SDS hammer in its class. Powerful hammer mechanism delivers 2.5 J of impact energy at low 8.9 m/s² vibrations.
- Compact, ergonomic design for increased enduser comfort.
- All metal gear case - optimum seating of the gears for enhanced service life.

	M18 CH-502C
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
Blow energy (EPTA)(J)	2.5
Charger supplied	59 min
Max. drilling concrete (mm)	26
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Max. percussion rate (bpm)	0 - 4900
No load speed (rpm)	0 - 1400
No. of batteries supplied	2
Sound power level (dB(A))	101.7
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	90.7
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Side handle, depth gauge, grease
Supplied in	Kitbox
Vibration chiseling (m/s²)	9.5
Vibration chiselling uncertainty (m/s²)	1.5
Vibration drilling (m/s²)	8.9
Vibration drilling into concrete [m|s²]	8,9
Vibration drilling uncertainty (m/s²)	1,5
Voltage (V)	18
Weight with battery pack (kg)	3.4