# M28 CHPX-502X | M28 FUEL™ 4-mode SDS-plus hammer with FIXTEC chuck

- Milwaukee® designed and built brushless POWERSTATE™ motor.
- Fuel gauge displays remaining battery charge.
- Compatible with M18-28 CPDEX dust extractor.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- High powered motor gives corded tool performance.
- Hardest hitting cordless SDS hammer in its class. Powerful hammer mechanism: delivers 4.1 J of impact energy at low 8.1 m/s² vibrations thanks to the new dual rail anti-vibration system.

| | M28 CHPX-502X |
|---|---|
| Battery pack capacity (Ah) | 5.0 |
| Battery type | Li-ion |
| Blow energy (EPTA)(J) | 4.1 |
| Charger supplied | 90 min |
| Max. drilling concrete (mm) | 28 |
| Max. drilling steel (mm) | 13 |
| Max. drilling wood (mm) | 30 |
| Max. percussion rate (bpm) | 0 - 5000 |
| No load speed (rpm) | 0 - 1350 |
| No. of batteries supplied | 2 |
| Optimised drilling capacity in concrete (mm) | ø 7 - 24 |
| Sound power level measured (dB(A)) | 103.7 |
| Sound power level measured uncertainty (dB(A)) | 3.0 |
| Sound pressure level (dB(A)) | 92.7 |
| Sound pressure level uncertainty (dB(A)) | 3.0 |
| Standard equipment | Side handle, depth gauge, grease, FIXTEC 13 mm full metal chuck |
| Supplied in | HD Box |
| Vibration chiseling (m/s²) | 8.1 |
| Vibration chiselling uncertainty (m/s²) | 1,5 |
| Vibration drilling (m/s²) | 8.1 |
| Vibration drilling into concrete [m\|s²] | 8.1 |
| Vibration drilling into concrete uncertainty [m\|s²] | 1.5 |
| Voltage (V) | 28 |