















M	HSS	HSS-E	DIN 376	ISO 2-6H	ISO 6HX
---	-----	-------	---------	----------	---------

Filettatura metrica ISO DIN 13 passo grosso																
			Anello rosso		Anello verde		Anello rosso Nitruato		Anello verde		Anello viola Vaporizzato		Nitruato			
			F 7863/3		F 7863/4		F 7865/3		F 7865/4		F 7865/5		F 7868		F 7871	
Modello			6245 Grulo-Spez.-R		6345 Grulo-Spez.-G		7255 Rapid-Spez.-R		7275 Rapid-VA-G		7235 Rapid V4A		6008 C-GG		6044 Grulo-Alu	
DIN			376		376		376		376		376		376		376	
Esecuzione/Forma			C/Elica destra 40°		C/Elica destra 40°		B/Imbocco corretto		B/Imbocco corretto		C/Imbocco corretto		C/Nitruati		C/Elica destra 45°	
Acciaio			HSS-E		HSS-E		HSS-E		HSS-E		HSS-E		HSS-E		HSS-E	
Tolleranza			ISO 2-6H		ISO 2-6H		ISO 2-6H		ISO 2-6H		ISO 6HX		ISO 6HX		ISO 2-6H	
Per fori																
Per materiali gruppo:			1.3.1 - 1.3.2 5.1		1.4 - 1.6 3.1 - 3.2.1		1.3.1 - 1.3.2 5.1		1.2 - 1.4 - 1.6 3.1 - 3.2.1		1.4 - 1.5 - 1.6 3.2.12.1 - 2.2		2.1 - 2.2		3.1	
M	Passo mm	Ø preforo mm	Codice F 7863	Cad. €	Codice F 7863	Cad. €	Codice F 7865	Cad. €	Codice F 7865	Cad. €	Codice F 7865	Cad. €	Codice F 7868	Cad. €	Codice F 7871	Cad. €
4	0,7	3,30	3004		4004		—		—		—		—		—	
5	0,8	4,20	—		4005		—		—		—		—		—	
6	1	5,00	3006		4006		—		4006		—		—		—	
8	1,25	6,80	3008		4008		—		4008		—		0008		0008	
10	1,5	8,50	3010		4010		3010		4010		—		0010		0010	
12	1,75	10,20	3012		4012		3012		4012		5012		0012		—	
14	2	12,00	3014		4014		3014		4014		5014		—		0014	
16	2	14,00	3016		4016		3016		4016		5016		0016		—	
18	2,5	15,50	3018		4018		3018		4018		—		0018		0018	
20	2,5	17,50	3020		4020		3020		4020		—		—		—	
22	2,5	19,50	—		4022		—		4022		—		0022		0022	
24	3	21,00	—		4024		—		4024		—		—		0024	
27	3	24,00	—		4027		—		—		—		0027		—	