











MF	HSS-E	DIN 374	DIN 357	ISO 2-6H
----	-------	---------	---------	----------

Filettatura metrica ISO DIN 13 passo fine												
					Anello rosso		Anello verde				Per dadi	
			F 7887		F 7888/3		F 7888/4		F 7889		F 7900	
Modello			7011 Rapid		6245 Grulo Spez.-R		6245 Grulo Spez.-G		6044 Grulo-Alu		8000	
DIN			374		374		374		374		357	
Esecuzione/Forma			B/Imbocco corretto		C/Elica destra 40°		C/Elica destra 40°		C/Elica destra 45°		Imbocco per dadi	
Acciaio			HSS-E		HSS-E		HSS-E		HSS-E		HSS-E	
Tolleranza			ISO 2-6H		ISO 2-6H		ISO 2-6H		ISO 2-6H		ISO 2-6H	
Per fori												
Per materiali gruppo:			1.1		1.3.1 - 1.3.2 5.1		1.4 - 1.6 3.1 - 3.2.1		3.1		Acciai legati fino a 900 N/mm ²	
M	Passo mm	Ø preforo mm	Codice F 7887	Cad. €	Codice F 7888	Cad. €	Codice F 7888		Codice F 7889	Cad. €	Codice F 7900	Cad. €
5	0,5	4,50	—		—		—		0505		—	
6	0,75	5,20	—		—		4607		0607		0607	
7	0,75	6,20	—		—		—		—		0707	
8	1	7,00	0810		—		4810		—		—	
9	1	8,00	—		—		—		—		0910	
10	1	9,00	0101		3101		4101		—		0101	
10	1,25	8,75	0102		—		—		—		—	
12	1,5	10,50	0125		3125		4125		—		0125	
14	1,5	12,50	0145		3145		4145		—		—	
16	1,5	14,50	0165		3165		4165		—		—	
18	1,5	16,50	0185		3185		4185		—		0185	
20	1,5	18,50	0205		3205		—		—		—	