

G **HSS-E** **DIN 5156**

Filettatura gas cilindrica
DIN ISO 228



F 7916

F 7918

F 7919

F 7920

Modello	7011 Rapid	6002	6030-Rsp	6040 Grulo
DIN	5156	5156	5156	5156
Esecuzione/Forma	B/Imbocco corretto	C	C/Elica destra 15°	C/Elica destra 40°
Acciaio	HSS-E	HSS-E	HSS-E	HSS-E
Per fori				

Per materiali gruppo: **1.1** **1.1** **1.1** **1.1**

G	Filetti per pollice	Ø preforo mm	Codice	Cad. €	Codice	Cad. €	Codice	Cad. €	Codice	Cad. €
1/8	28	8,80	F 7916 0018		F 7918 0018		F 7919 0018		F 7920 0018	
1/4	19	11,80	F 7916 0014		F 7918 0014		F 7919 0014		F 7920 0014	
3/8	19	15,25	F 7916 0038		F 7918 0038		F 7919 0038		F 7920 0038	
1/2	14	19,00	F 7916 0012		F 7918 0012		F 7919 0012		F 7920 0012	
5/8	14	21,00	F 7916 0058		—		F 7919 0058		F 7920 0058	
3/4	14	24,50	F 7916 0034		F 7918 0034		F 7919 0034		F 7920 0034	
7/8	14	28,25	—		—		F 7919 0078		F 7920 0078	
1	11	30,75	F 7916 0001		F 7918 0001		F 7919 0001		F 7920 0001	
1 1/8	11	35,50	—		F 7918 0118		F 7919 0118		—	
1 3/8	11	41,50	F 7916 0138		F 7918 0138		F 7919 0138		—	

Tabella per la scelta dei maschi e indicazioni sui rivestimenti, vedere pag. 534+537