

Con tagliente frontale al centro - Esecuzione lunga

| | | | | | | | |
|--------------|------------|--|-----------|--|-------|--|-----|
| HSS Co 8% | DIN 844 | | Tipo N | | t = 2 | | e 8 |
|--------------|------------|--|-----------|--|-------|--|-----|



| Ø mm | Codice | F 8003 Cad. € | Lungh. taglienti mm | Lungh. totale mm | Gambo Ø mm h 7 | Ø mm | Codice | F 8003 Cad. € | Lungh. taglienti mm | Lungh. totale mm | Gambo Ø mm h 7 |
|------|-------------|------------------|---------------------------|------------------------|----------------------|------|-------------|------------------|---------------------------|------------------------|----------------------|
| 7 | F 8003 0007 | | 16 | 80 | 10 | 19 | F 8003 0019 | | 32 | 123 | 16 |
| 11 | F 8003 0011 | | 22 | 102 | 12 | 24 | F 8003 0024 | | 45 | 166 | 25 |
| 13 | F 8003 0013 | | 26 | 110 | 12 | 25 | F 8003 0025 | | 45 | 166 | 25 |
| 15 | F 8003 0015 | | 26 | 110 | 12 | 26 | F 8003 0026 | | 45 | 166 | 25 |
| 16 | F 8003 0016 | | 32 | 123 | 16 | 28 | F 8003 0028 | | 45 | 166 | 25 |
| 18 | F 8003 0018 | | 32 | 123 | 16 | | | | | | |


Frese cilindriche a testa semisferica

Con tagliente frontale al centro

Esecuzione corta

NORMEX®
a brand of **ABC**

| | | | | | | | |
|--------------|------------|--|-----------|--|-------|--|------|
| HSS Co 8% | DIN 327 | | Tipo N | | t = 2 | | h 10 |
|--------------|------------|--|-----------|--|-------|--|------|



| Ø mm | Codice | F 8004 Cad. € | Lungh. taglienti mm | Lungh. totale mm | Gambo Ø mm h 7 | Ø mm | Codice | F 8004 Cad. € | Lungh. taglienti mm | Lungh. totale mm | Gambo Ø mm h 7 |
|------|-------------|------------------|---------------------------|------------------------|----------------------|------|-------------|------------------|---------------------------|------------------------|----------------------|
| 4 | F 8004 0004 | | 7 | 51 | 6 | 12 | F 8004 0012 | | 16 | 73 | 12 |
| 5 | F 8004 0005 | | 8 | 52 | 6 | 14 | F 8004 0014 | | 16 | 73 | 12 |
| 6 | F 8004 0006 | | 8 | 52 | 6 | 16 | F 8004 0016 | | 19 | 79 | 16 |
| 8 | F 8004 0008 | | 11 | 61 | 10 | 18 | F 8004 0018 | | 19 | 79 | 16 |
| 10 | F 8004 0010 | | 13 | 63 | 10 | 20 | F 8004 0020 | | 22 | 88 | 20 |

(E.C.) HITACHI®

| | | | | | | | |
|--------------|------------|--|-----------|--|-------|--|------|
| HSS Co 8% | DIN 327 | | Tipo N | | t = 2 | | h 10 |
|--------------|------------|--|-----------|--|-------|--|------|



| Ø mm | Codice | F 8005 Cad. € | Lungh. taglienti mm | Lungh. totale mm | Gambo Ø mm h 7 | Ø mm | Codice | F 8005 Cad. € | Lungh. taglienti mm | Lungh. totale mm | Gambo Ø mm h 7 |
|------|-------------|------------------|---------------------------|------------------------|----------------------|------|-------------|------------------|---------------------------|------------------------|----------------------|
| 4 | F 8005 0004 | | 7 | 51 | 6 | 14 | F 8005 0014 | | 16 | 73 | 12 |
| 5 | F 8005 0005 | | 8 | 52 | 6 | 16 | F 8005 0016 | | 19 | 79 | 16 |
| 8 | F 8005 0008 | | 11 | 61 | 10 | 18 | F 8005 0018 | | 19 | 79 | 16 |
| 10 | F 8005 0010 | | 13 | 63 | 10 | 20 | F 8005 0020 | | 22 | 82 | 16 |
| 12 | F 8005 0012 | | 16 | 73 | 12 | | | | | | |

Esecuzione lunga

NORMEX®
a brand of **ABC**

| | | | | | | | |
|--------------|------------|--|-----------|--|-------|--|------|
| HSS Co 8% | DIN 327 | | Tipo N | | t = 2 | | h 10 |
|--------------|------------|--|-----------|--|-------|--|------|



| Ø mm | Codice | F 8006 Cad. € | Lungh. taglienti mm | Lungh. totale mm | Gambo Ø mm h 7 | Ø mm | Codice | F 8006 Cad. € | Lungh. taglienti mm | Lungh. totale mm | Gambo Ø mm h 7 |
|------|-------------|------------------|---------------------------|------------------------|----------------------|------|-------------|------------------|---------------------------|------------------------|----------------------|
| 4 | F 8006 0004 | | 11 | 63 | 6 | 12 | F 8006 0012 | | 26 | 110 | 12 |
| 5 | F 8006 0005 | | 13 | 68 | 6 | 14 | F 8006 0014 | | 26 | 110 | 12 |
| 6 | F 8006 0006 | | 13 | 68 | 6 | 16 | F 8006 0016 | | 32 | 123 | 16 |
| 8 | F 8006 0008 | | 19 | 88 | 10 | 18 | F 8006 0018 | | 32 | 123 | 16 |
| 10 | F 8006 0010 | | 22 | 95 | 10 | 20 | F 8006 0020 | | 38 | 141 | 20 |

(E.C.) HITACHI®

| | | | | | | | |
|--------------|----------------------|--|-----------|--|-------|--|------|
| HSS Co 8% | Norme di fabbrica | | Tipo N | | t = 2 | | h 10 |
|--------------|----------------------|--|-----------|--|-------|--|------|



| Ø mm | Codice | F 8007 Cad. € | Lungh. taglienti mm | Lungh. totale mm | Gambo Ø mm h 7 | Ø mm | Codice | F 8007 Cad. € | Lungh. taglienti mm | Lungh. totale mm | Gambo Ø mm h 7 |
|------|-------------|------------------|---------------------------|------------------------|----------------------|------|-------------|------------------|---------------------------|------------------------|----------------------|
| 8 | F 8007 0008 | | 19 | 88 | 10 | 18 | F 8007 0018 | | 32 | 123 | 16 |
| 12 | F 8007 0012 | | 26 | 110 | 12 | 20 | F 8007 0020 | | 38 | 135 | 16 |
| 14 | F 8007 0014 | | 26 | 110 | 12 | | | | | | |